

Model	VT2070-H1ETR-31	VT2070-N0CTR-24	VT2104-H0ETR-51
Ethernet Port	1	None	1
USB Programming Port	1		1
USB Device Port	1		1
COM Port	COM1:RS232(DB9) COM2: RS422/RS485(DB9) COM3: RS485(DB9)	COM1:RS232(DB9) COM2: RS422/RS485(DB9)	COM1:RS232(DB9) COM2: RS422/RS485(DB9) COM3: RS485(DB9) COM4: RS485(5-Pin) COM5: RS485(5-Pin)
Display Specifications	7"(True color TFT)		10.4"(True color TFT)
Resolution	800x480		800x600
Brightness(cd/m ²)	400		400
Colour	65,536		65,536
Backlight Life	20,000 Hours		20,000 Hours
Touchpad	4-wire resistive		4-wire resistive
CPU	RISC ARM9 32bits 300MHz		
Program flash	128MB		
Battery backup memory	128KB	1MB	128KB
User Memory	64M		64M
Power Supply	DC24V(±10%)		DC24V(±10%)
Power Consumption	20W		20W
CE Certification	CE		CE
Protection Level(front panel)	IP66		IP66
Working Temperature	-10~50℃		-10~50℃
Working Humidity	10%90%		10%-90%