

NE-24


PATLITE



- LED
- Φ57
- IP65
- NPN/PNP Open collector

Enhanced Illumination : Use of long-lived super bright LED.
Energy Efficient : Low power consumption.
Maintenance-Free : High vibration resistant and No bulb replacement needed.
Terminal Block : For easy wiring
Applications : Suitable for small machine tools, switchboard, etc

Model	NE-24				
Rated voltage	DC 24V (No Polarity) NPN/PNP open collector				
Operating voltage	Operating voltage DC 21.6V ~26.4V				
Current Consumption	Red 30mA	Amber 30mA	Green 50mA	Blue 50mA	Clear 50mA
Operating temperature range(Relative humidity)	-30°C~+ 60°C (Less than 90%)				
Mounting place	Indoor & Outdoor				
Mounting direction	Upright, Updown & Horizontal				
Protection rating	IP65				
Vibration proof	19.6m/s ²				
Insulation resistance	To be measured by an insulation measuring device of 500VDC between the terminals and the chassis. More than 1MΩ				
Withstand voltage	500VAC being applied between the terminals and the chassis for 1 minute. Not breaking insulation.				
Luminous intensity	Red 650mcd	Amber 1200mcd	Green 1500mcd	Blue 300mcd	Clear 1200mcd
Mass	50g				



CAUTION
 To ensure correct use of these products, read the Instruction Manual prior to use. Failure to follow all safeguards can result in fire, electric shock, or other accidents. Specifications are subject to change without notice.



For the benefit of mankind and the earth, Patlite is committed to developing environmentally friendly products.

PATLITE Corporation